

AUTEL®

# MaxiCharger

## AC Lite – 7.4kW



# Technical Specifications

---

## Product Information

Charging mode	Type 2
Input/output power rating and current	Single phase up to 7.4kW/32A
Input/output voltage	230V±15%, single phase; 50Hz
Network type	TT, TN
Connector type	IEC 62196 type 2 plug, 5m
Internal RCD	AC 30mA, DC 6mA
Protection	Overcurrent, overvoltage, undervoltage, integrated surge protection
Power measurement accuracy	±2% accuracy class

---

## General Characteristics

IP and IK rating	IP65, IK08
Operating altitude	2000m
Operating temperature range	-30°C~+50°C
Storage temperature range	-40°C~+70°C
Mounting	Wall or floor using a pedestal
Dimensions (H×W×D)	336 x 187 x 97 mm

---

## User Interface

Status indication	LED/APP
User interface	Autel Charge APP; Autel Charge Cloud
Connectivity	Bluetooth, Wi-Fi
Communication protocols	OCPP 1.6J (Autel cloud only)
User authentication	APP, RFID card, Autostart

---

## Software Update

OTA updates via web portal

---

## Certification and Standards

Safety and compliance	IEC 61851-1, IEC 62311, IEC 62479, IEC 62955, IEC 61439-1/ -7
CertificationCodes and standards	CE (TUV)
Warranty	2 years
Fire class	UL94 V0
Overvoltage category	III
OCPP Compability Test	OCA
Product Design Life	More than 10 years

---

\* All pictures shown are for illustration purpose only. Actual product and specifications may vary due to product enhancement

**AUTEL**<sup>®</sup>